



SHELL SIZE	A THREAD	B MAX	C MAX	D MAX	E MAX	F MAX
09	M12 x 1.0	18,0	13,1	24,8	25,5	28,5
11	M15 x 1.0	21,0	13,9	25,5	26,5	30,2
13	M18 x 1.0	24,5	14,5	26,1	31,0	31,7
15	M22 x 1.0	27,5	15,5	26,7	37,0	33,2
17	M25 x 1.0	31,0	16,1	27,5	40,0	34,9
19	M28 x 1.0	34,0	16,8	28,5	44,5	36,5
21	M31 x 1.0	37,0	17,1	28,8	49,0	38,1
23	M34 x 1.0	40,0	17,7	29,1	51,5	38,6
25	M37 x 1.0	43,5	18,4	30,0	53,0	41,1

ENTRY SIZE	G	H LENGTH	J LENGTH	CABLE DIA RANGE
05	7,92	60	40	4,5 - 9,0
08	12,70	60	40	6,0 - 12,0
10	15,88	72	48	7,5 - 15,0
12	19,05	72	48	9,0 - 18,0
16	25,40	95	55	10,0 - 25,0
20	31,80	125	70	12,5 - 25,0
24	38,10	125	70	15,0 - 36,0

**TAKSH1-17-08-1-C-UB**

SERIES \_\_\_\_\_  
 CONNECTOR INTERFACE \_\_\_\_\_  
 ANGLE \_\_\_\_\_  
 SHELL SIZE \_\_\_\_\_  
 ENTRY SIZE \_\_\_\_\_  
 MATERIAL \_\_\_\_\_  
 PLATING \_\_\_\_\_  
 HEAT SHRINK TERMINATION: UB - UNSCREENED BOOT \_\_\_\_\_  
 SB - SCREENED BOOT \_\_\_\_\_

HEAT SHRINK ADAPTOR	<b>SERIES TAK</b> TO FIT CONNECTOR CODE H
	THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY
 <b>POLAMCO LTD</b>	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP